

Package: gto (via r-universe)

August 26, 2024

Type Package

Title Insert 'gt' Tables into Word Documents

Version 0.1.1

Description Insert tables created by the 'gt' R package into 'Microsoft Word' documents. This gives users the ability to add to their existing word documents the tables made in 'gt' using the familiar 'officer' package and syntax from the 'officeverse'.

License Apache License (>= 2)

Encoding UTF-8

Imports gt (>= 0.8.0), magrittr, officer, rlang, xml2

Suggests testthat (>= 3.0.0), dplyr, tibble, covr

RoxygenNote 7.2.1

Config/testthat/edition 3

NeedsCompilation no

Author Ellis Hughes [aut, cre]
(<https://orcid.org/0000-0003-0637-4436>), GlaxoSmithKline
Research & Development Limited [cph, fnd]

Maintainer Ellis Hughes <ellis.h.hughes@gsk.com>

Date/Publication 2023-04-03 18:50:08 UTC

Repository <https://thebioengineer.r-universe.dev>

RemoteUrl <https://github.com/cran/gto>

RemoteRef HEAD

RemoteSha a828f5b5a4ecab6317d8cdc495bea43467b4c458

Contents

body_add_gt	2
Index	4

body_add_gt	<i>Add 'gt' table into a Word document</i>
-------------	--

Description

Add a 'gt' table into a Word document. The table will be processed using the [as_word](#) function then inserted either after, before, or on the cursor location.

Usage

```
body_add_gt(
    x,
    value,
    align = "center",
    pos = c("after", "before", "on"),
    caption_location = c("top", "bottom", "embed"),
    caption_align = "left",
    split = FALSE,
    keep_with_next = TRUE
)
```

Arguments

x	'rdocx' object
value	'gt_tbl' object
align	left, center (default) or right.
pos	where to add the gt table relative to the cursor, one of "after" (default), "before", "on" (end of line).
caption_location	top (default), bottom, or embed indicating if the title and subtitle should be listed above, below, or be embedded in the table
caption_align	left (default), center, or right. Alignment of caption (title and subtitle). Used when 'caption_location' is not "embed".
split	set to TRUE if you want to activate Word option 'Allow row to break across pages'.
keep_with_next	Word option 'keep rows together' can be activated when TRUE. It avoids page break within tables.

Value

An updated rdocx object with a 'gt' table inserted

See Also

`flextable::body_add_flextable()`

Examples

```
library(officer)
library(gt)

gt_tbl <- gt(head(exibble))

doc <- read_docx()
doc <- body_add_gt(doc, value = gt_tbl)
fileout <- tempfile(fileext = ".docx")
print(doc, target = fileout)
```

Index

as_word, [2](#)

body_add_gt, [2](#)